

# ATP eUSB Industrial Grade

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



The ATP eUSB module employs the widely supported USB interface, making it a suitable boot device and efficient data storage solution.

Ideal for industrial and rugged environments, the eUSB module is cost-effective and offers data transfer efficiency in a wide range of applications such as networking, embedded and medical applications that previously used the Intel® Z-U130 Value SSD.

Featuring PowerProtector technology with built-in hardware-based power backup circuit, ATP eUSB delivers reliable controller and lasting NAND flash operation even during sudden power-loss events.

#### **Key Features**

- Global wear leveling
- PowerProtector

### **Applications**

- Networking
- Embedded
- Medical applications



## **Specifications**

Product Name		eUSB						
Product Line		Premium	Superior	Superior				
Naming		B800Pi	B600Sc	B600Sc				
Flash Type		SLC	MLC	MLC				
Density		1 GB to 32 GB	8 GB to 32 GB	16 GB to 64 GB				
Performance	Sequential Read up to (MB/s)	30	25	44				
	Sequential Write up to (MB/s)	25	19	17				
Interface		Compatible with USB 2.0 (480 Mbps)						
Operating Temperature		-40°C to 85°C	o 70°C					
Endurance	TBW* (max.)	1,280 TB	38.4 TB	>76.8 TB**				
	DWPD* (max.)	37.4	1.7	>1.7**				
Reliability	MTBF @ 25°C	>5,000,000 hours	>2,000,000 hours	>2,000,000 hours				
	Number of Insertions	10,000 minimum						
Dimensions: L x W x H (mm)		36.9 x 26.6 x 9.5						
Connector Pin Pitch***		2.54	2.54 mm / 2.00mm					

<sup>\*</sup> Under highest Sequential write value. May vary by density, configuration and applications.

<sup>\*\*\*</sup> By project support.

Technologies & Add-On Services*		S.M.A.R.T.	PowerProtector	Advanced Wear Leveling	Dynamic Data Refresh	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating
Product Line	Premium	•	•	•	•	•	Δ	Δ
	Superior	•	•	•	Δ		Δ	Δ

Δ: Customization option available on a project basis.

## To learn more about this product, contact your ATP Representative.

ATP Global Footprint

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com

<sup>\*\*</sup> Estimated endurance only.