

ATP SD/SDHC/SDXC Card Industrial Grade

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications









Key Features

- SD Life Monitor
- Dynamic Data Refresh
- Power failure protection
- Industrial temperature
- 100% MP Level Test

ATP SD cards are the ideal storage format for industrial and automotive applications as they can be conveniently inserted into and easily removed from small host devices for convenient data transfer and storage expansion.

Made to perform dependably under rigorous conditions, ATP SD cards are designed with extensive longevity, which is typically required in industrial applications such as automation, networking, health care and more.

ATP SD cards also deliver the quality, durability and reliability to meet the requirements of major automotive OEM/Tier 1 suppliers, system developers and service providers for higher levels of data accuracy, consistency and integrity in applications such as maps/navigation systems, in-vehicle infotainment (IVI), Advanced Driver Assistance Systems (ADAS), and other data- intensive applications. These solutions can withstand extreme temperatures, dust and shock/vibration, and maintain data integrity under power cycling or sudden power-off events.

Now available in 3D triple-level cell (TLC) NAND flash with A1 Performance Class rating, ATP SD cards undergo endurance, data retention and wide temperature tests and are certified according to international, automotive-specific and temperature-related standards.



▲: Customization option available on a project basis.

PRODUCT FLYER | SD

Specifications

SD/SDHC/SDXC							
Product Line	Premium		Superior				
	S800Pi	S700Pi	S700Sc	S650Si	S650Sc		
Interface	512 MB to 2 GB, HS mode 4 GB to 8 GB, UHS-I	UHS-I	UHS-I				
Flash Type	SLC	3D Pseudo SLC	3D Pseudo SLC	3D TLC			
Form Factor			SD Card				
Operating Temperature	-40°C to 85°C		-25°C to 85°C	-40°C to 85°C	-25°C to 85°C		
Power Loss Protection Options	Firmware Based						
Optional SED Features			-				
Capacity	512 MB to 8 GB	8 GB to 64 GB	8 GB to 64 GB	32 GB to 128 GB			
	Performance						
Sequential Read (MB/s) up to	70	95	95	96			
Sequential Write (MB/s) up to	39	62	62	62			
	Endurance and Reliability						
Endurance (TBW)1 up to	192 TB	512 TB	512 TB	256 TB			
Reliability MTBF @ 25°C	>5,000,000 hours	>3,000,000 hours	>3,000,000 hours	>2,000,000 hours			
Reliability Number of Insertions	20,000 (SDA spec minimum 10,000)						
	Others						
Dimensions: L x W x H (mm)	32.0 x 24.0 x 2.1						
Certifications	CE, FCC, UKCA, RoHS						
Warranty	5 years		2 years				

SD/SDHC/SDXC							
Product Line	Superior						
Product Line	S600Si	S600Sc	S600Sia	S600Sc			
Interface	UHS-I						
Flash Type	3D TLC MLC 3D TLC						
Form Factor	SD Card						
Operating Temperature	-40°C to 85°C	-25°C to 85°C	-40°C to 85°C	-25°C to 85°C			
Power Loss Protection Options	Firmware Based						
Optional SED Features	-						
Capacity	32 GB to 256 GB 4 GB to 64 GB 32 GB to 256 GB						
	Performance						
Sequential Read (MB/s) up to	96	87	96				
Sequential Write (MB/s) up to	65 58 65		5				
	Endurance and Reliability						
Endurance (TBW)1 up to	Endurance (TBW) ¹ up to 307 TB		307 TB				
Reliability MTBF @ 25°C	>2,000,000 hours						
Reliability Number of Insertions	20,000 (SDA spec minimum 10,000)						
	Others						
Dimensions: L x W x H (mm)	32.0 x 24.0 x 2.1						
Certifications	CE, FCC, UKCA, RoHS						
Warranty	2 years						

¹ Under highest Sequential write value. May vary by density, configuration and applications.

Product spec and its related information are subject to change without advance notice. Please refer to $\underline{www.atpinc.com}$ for latest information

v1.0 202201

© Copyright 2022 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

ATP TAIWAN (HQ)

ATP USA

ATP EUROPE

TEL: +49-89-374-9999-0 sales-europe@atpinc.com

ATP JAPAN

ATP CHINA

TEL: +81-3-6260-0797 sales-japan@atpinc.com