




USB 2.0 eUSB

The Global Leader in Specialized Storage and Memory Solutions



Key Features

- Superior Random Write Performance
- Global wear leveling
- Power Loss Protection
- Hardware Write Protect*

* May vary by product and project support








The ATP eUSB module employs the widely supported USB interface, making it a suitable boot device and efficient data storage solution.

Ideal for industrial and rugged environments, the eUSB module is cost-effective and offers data transfer efficiency in a wide range of applications such as networking, embedded and medical applications that previously used the Intel® Z-U130 Value SSD.

With Power Loss Protection technology options featuring built-in hardware-based power backup circuit and/or firmware-based solution, ATP eUSB delivers reliable controller and lasting NAND flash operation even during sudden power-loss events.

Specifications

USB 2.0 eUSB			
Product Line	Premium		Superior
	B800Pi	B800Pi	B600Sc
Interface	Compatible with USB 2.0 (480 Mbps)		
Flash Type	SLC		MLC
Form Factor	Pitch 2.54 mm / 2.00 mm		
Operating Temperature	-40°C to 85°C		0°C to 70°C
Power Loss Protection Options	Firmware Based	Hardware + Firmware Based	
Optional SED Features	-		
Capacity	1 GB to 16 GB	1 GB to 32 GB	8 GB to 32 GB
Performance			
Sequential Read (MB/s) up to	36	30	25
Sequential Write (MB/s) up to	23	25	19
Endurance and Reliability			
Endurance (TBW) ¹ up to	1,548 TB	1,280 TB	38.4 TB
Reliability MTBF @ 25°C	>5,000,000 hours		>2,000,000 hours
Reliability Number of Insertions	10,000 minimum		
Others			
Dimensions (mm)	36.9 x 26.6 x 9.5		
Certifications	CE, FCC, UKCA, RoHS		
Warranty	5 years		2 years

Technologies & Add-On Services	 S.M.A.R.T.	 Firmware-based Power Loss Protection	 Hardware-based Power Loss Protection	 Advanced Wear Leveling	 Industrial Temperature	 Anti-Sulfur Resistors	 Conformal Coating
Premium	○	○	▲	○	○	▲	▲
Superior	○	○	▲	○	—	▲	▲

¹ Under highest Sequential write value. May vary by density, configuration and applications.
 ▲: Customization option available on a project basis.

Product spec and its related information are subject to change without advance notice.
 Please refer to www.atpinc.com for latest information

v1.0 012023

© Copyright 2022 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
 sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
 sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
 sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
 sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
 sales@cn.atpinc.com