

## CFast card

The Global Leader in Specialized Storage and Memory Solutions



## **KEY FEATURES**

- Advanced wear leveling algorithm
- Bad block management
- AutoRefresh technology
- Power Loss Protection
- S.M.A.R.T

ATP CFast cards combine the convenient and trusted format of CompactFlash with the speed, capacity and performance of SATA III, while maintaining backward compatibility with other SATA versions.

They are recommended as boot and storage devices in embedded and industrial applications such as avionics/aerospace, automation, marine navigation, telecommunication/networking and medical equipment where mission-critical data requires the highest level of reliability, durability and data integrity.

Special features and technologies include: optional Power Loss Protection, which provides a hardware-based backup power circuit and/or firmware-based solution during a power failure; Advanced Wear Leveling for higher endurance and longer product life span; ECC (error correction code) and AutoRefresh technologies, which correct and monitor the error bit levels to ensure data integrity in frequently read areas, and S.M.A.R.T. (Self-Monitoring, Analysis, and Reporting Technology) function for easy monitoring of various device health parameters to help predict storage failure for preventive action.

## **Specifications**

CFast Card										
Product Line	Premium A800Pi									
Interface	SATA III 6 Gb/s									
Flash Type	SLC									
Form Factor	CFast Type I									
Operating Temperature	-40°C to 85°C									
Power Loss Protection Options	Hardware + Firmware Based									
Optional SED Features	-									
Capacity	8 GB to 32 GB									
	Performance									
Sequential Read (MB/s) up to	500									
Sequential Write (MB/s) up to	300									
Random Reads IOPS up to	35,800									
Random Writes IOPS up to	-									
	Endurance and Reliability									
Endurance (TBW)1 up to	2,667 TB									
Reliability MTBF @ 25°C	>2,000,000 hours									
Reliability Number of Insertions	10,000 minimum									
	Others									
Dimensions (mm)	36.4 x 42.8 x 3.6									
Certifications	CE, FCC, UKCA, RoHS									
Warranty	5 years									

Technologies & Add-On Services		Firmware-based Power Loss Protection	Hardware-based Power Loss Protection		Advanced Wear Leveling	Dynamic Data Refresh	Secure Erase	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating	Joint Validation
Premium	0	0	<b>A</b>	0	0	0	0	0	<b>A</b>	<b>A</b>	<b>A</b>

- 1 Under highest Sequential write value. May vary by density, configuration and applications.
- ▲: Customization option available on a project basis.

Product spec and its related information are subject to change without advance notice. Please refer to <a href="www.atpinc.com">www.atpinc.com</a> for latest information

v1.0 022024

 $^{\odot}$  Copyright 2024 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

## **WE BUILD WITH YOU**

TEL: +1-408-732-5000

sales@atpinc.com