




# SDRAM

The Global Leader in Specialized Storage and Memory Solutions



## KEY FEATURES

- Legacy system support

Synchronous Dynamic Random Access Memory (SDRAM) is the common term for PC133 single data rate (SDR) SDRAM, with clock frequencies of 133 MHz. ATP is committed to providing customers with the highest reliability products and offers custom screening services to help them meet specialized or unique application requirements.

## Specifications

SDRAM	
DIMM Type	Non-ECC SO-DIMM
Density	64 MB to 256 MB
Speed up to (MT/s)	133
PCB Height	Low Profile
Operating Temperature	0°C to 70°C

Technologies & Add-On Services	30µm Golden Finger	ATP TDBI
Non-ECC SO-DIMM	●	●

Product spec and its related information are subject to change without advance notice. Please refer to [www.atpinc.com](http://www.atpinc.com) for latest information

v1 022024

© Copyright 2024 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

# WE BUILD WITH YOU

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368  
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000  
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0  
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797  
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220  
sales@cn.atpinc.com