

CompactFlash card

The Global Leader in Specialized Storage and Memory Solutions





KEY FEATURES

- Global wear leveling and bad block management
- AutoRefresh technology
- Power Loss Protection

- Power saving mode
- S.M.A.R.T support

CompactFlash cards in the original IDE/PATA interface continue to enjoy wide usage in industrial and embedded environments due to their durability and rugged build.

ATP's industrial CompactFlash cards work best in high-throughput applications requiring speedy transfers of large blocks of data, such as high-definition videos and camera systems.

Industrial temperature-rated CompactFlash cards can operate in critical temperature ranges, from -40°C to 85°C. Superior flash management capabilities such as Advanced Wear Leveling, bad block management, and AutoRefresh technology ensure data integrity, reliability and longevity for a wide range of applications and workloads. Power Loss Protection options include firmware and/or hardware-based protection that prevents data loss or corruption due to power losses or fluctuations.

Specifications

CompactFlash Card										
Product Line	1800Pi	1700Sc	1600Sc							
Interface	UDMA 0~4	UDMA 0~6								
Flash Type	SLC	Pseudo SLC	MLC							
Form Factor	CF Type I									
Operating Temperature	-40°C to 85°C	0°C to 70°C								
Power Loss Protection Options	Hardware + Firmware Based	vare Based Firmware Based								
Optional SED Features		-								
Capacity	512 MB to 32 GB	8 GB to 16 GB	16 GB to 32 GB							
		Performance								
Sequential Read (MB/s) up to	61	110	108							
Sequential Write (MB/s) up to	55	80	46							
	Endurance and Reliability									
Endurance (TBW)1 up to	1,280 TB	128 TB	38 TB							
Reliability MTBF @ 25°C	>5,000,000 hours	>2,000,000 hours								
Reliability Number of Insertions	10,000 minimum									
	Others									
Dimensions (mm)	36.4 x 42.8 x 3.3									
Certifications	CE, FCC, RoHS, UKCA									
Warranty	5 years	5 years 2 years								

Technologies & Add-On Services	S.M.A.R.T.	Firmware-based Power Loss Protection			Advanced Wear Leveling	Dynamic Data Refresh	Industrial Temperature	Anti-Sulfur Resistors	Conformal Coating
Premium	0	0	0	0	0	0	0	A	A
Superior	0	0	_	0	0	0	_	A	A

¹ Under highest Sequential write value. May vary by density, configuration and applications.

Product spec and its related information are subject to change without advance notice. Please refer to $\underline{www.atpinc.com} \ \ for \ latest information$

v1.0 022024

 $^{\odot}$ Copyright 2024 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

TEL: +1-408-732-5000

sales@atpinc.com

^{▲:} Customization option available on a project basis.