



PCIe® Gen4 NVMe CFexpress Card

The Global Leader in Specialized Storage and Memory Solutions



KEY FEATURES

- Superior Read/Write performance
- Self-Encrypting Drive (SED) with AES 256-bit Encryption, TCG Opal 2.0*
- Host Memory Buffer (HMB) support
- Hardware Write Protect*

* Optional, by project support.

ATP N751Pi / N651Si / N601Sc CFexpress Type B memory cards support the NVMe™ protocol and utilize the PCIe 3.0 x2* interface. The N751Pi / N651Si / N601Sc surpasses standard configurations and delivers impressive high-speed sequential read/write speeds of up to 3500/3200 MB/s. Built with 3D TLC flash (available with pSLC by project support), ATP CFexpress Type B memory cards offer big storage for IPC/embedded, automation, networking, test and measurement, and transportation systems as well as other applications that require excellent reliability, endurance, and performance.

The N751Pi / N651Si / N601Sc features Host Memory Buffer (HMB) support to improve random read performance, optional TCG Opal 2.0 and hardware write-protect security, and software RAID 0, 1 compatibility. To ensure optimal sustained performance, the N651Si / N601Sc Series CFexpress cards continuously monitor device temperature and enable firmware-based throttling that adjusts performance without drastic drops.

*CFExpress spec 4.0 for PCIe Gen. 4 is under IP review and will be released Aug. 24, 2023.

Specifications

PCIe® Gen4 NVMe CFexpress Card			
Product Line	Premium	Superior	
	N751Pi	N651Si	N601Sc
Interface	PCIe G4 x2		
Flash Type	3D TLC (pSLC mode)	3D TLC	
Form Factor	CFexpress Type B		
Operating Temperature	-40°C to 85°C		0°C to 70°C
Power Loss Protection Options	Firmware Based		
Optional SED Features	AES 256-bit Encryption, TCG Opal 2.0		
Capacity	40 GB to 320GB	128 GB to 1 TB	
Performance			
Sequential Read (MB/s) up to	3,500		
Sequential Write (MB/s) up to	3,100	3,200	
Random Reads IOPS up to	770,000		
Random Writes IOPS up to	735,000	750,000	
Endurance and Reliability			
Endurance (TBW) ¹ up to	19,010 TB	4,065 TB	2,600 TB
Reliability MTBF @ 25°C	>2,000,000 hours		
Reliability Number of Insertions	10,000 minimum		
Others			
Dimensions (mm)	29.6 x 38.5 x 3.8		
Certifications	CE, FCC, RoHS, UKCA		
Warranty	5 years	2 years	

Technologies & Add-On Services														
Premium	○	○	○	○	○	○	○	▲	▲	○	▲	▲	○	▲
Superior	○	○	○	○	○	○	○	▲	▲	○	—	▲	○	▲

¹ Under highest Sequential write value. May vary by density, configuration and applications.
 ▲: Customization option available on a project basis.

Product spec and its related information are subject to change without advance notice.
 Please refer to www.atpinc.com for latest information

v1.1 052024

© Copyright 2024 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
 sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
 sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
 sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
 sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
 sales@cn.atpinc.com