

The Global Leader in Specialized Storage and Memory Solutions

# WE BUILD WITH YOU

# **ATP INDUSTRIAL ENTERPRISE SSD SERIES**



PRODUCT FLYER

# INTRODUCTION

Information Technology (IT) and Operational Technology (OT) are converging, resulting in the rise of Edge storage/computing that requires enterprise-class quality of service and industrial-grade reliability and endurance.

Enterprise storage/computing is becoming less centralized in data centers and controlled environments and becoming more distributed. Data is being driven to the edge where operating conditions are more extreme, locations are not easy to reach, and often, on the constant move. A new breed of storage solutions is needed, which combines the benefits of industrial solid-state drives (SSDs) and enterprise solutions.

The Industrial Enterprise N651Sie Series SSDs leverage NVMe PCIe Gen4x 4 and are available as M.2, U.2, and E1.S. They are built for the age of data deluge as centralized computing increasingly moves to the edge, and enterprise operations in uncontrolled environments become more prevalent.

They combine the best of enterprise and industrial features, making them excellent as boot drives, data storage drives, or mixed-use drives.

# IT/OT IT CONVERGENCE OT

encompasses the management of data, computer systems, and communication networks to facilitate information processing and sharing. refers to technology used in industrial and infrastructure systems to monitor and control physical processes, machinery, and equipment.

# The Best of Both Worlds

Why choose when you can have the Best of Both Worlds?

N651Sie PCIe Gen4 Wille M.2.SSD

INDUSTRIAL ENTERPRISE

## **BEST ENTERPRISE-CLASS FEATURES**

#### Endurance

- Boot: 1 DWPD
- Read Intensive: 2 DWPD
- Mixed Use/Write Intensive: 5 DWPD

#### **Data Retention**

- 1 year at 55°C (100% P/E cycles)
- Exceeds JESD219A standards for Enterprise-Class SSDs

#### **Consistent Performance for Enterprise Workloads**

- Sequential Read/Write: up to 6,450/6,050 MB/s
- High Sustained Sequential/Random Write: up to 3,200/1,280 MB/s

#### High Quality of Service (QoS)

- M.2: Read <90µs, Write <10µs
- U.2 and E1.S: Read <80µs, Write <10µs Reliability
  - Very low uncorrectable bit error rate (UBER) of less than 1 in 10^17
  - Validated through End-of-Life testing and Reliability Demonstration Testing (RDT)

#### **BEST INDUSTRIAL-GRADE ADVANTAGES**

🖅 😰 INDUSTRIAL ENTERPRISE

N651Sie PCle Gen4 NVMc E1.5 5

#### I-Temp Support

Reliable operation from -40°C to 85°C

#### Robust Cross-Temp Error Handling Solution

- Maintains data integrity under severe temperature changes
- Ensures reliability even towards the device's end of life

#### **Thermal Management**

- Adaptive thermal throttling
- Customizable temperature settings
- Heatsink and graphite options for excellent heat dissipation

#### Hardware Power Loss Protection (HW PLP)

- Protects stored data and data in transit
- Prevents data loss or corruption
- Essential for high-performance computing environments running 24/7

# WE BUILD WITH YOU Firmware Customization Service

Under ATP's WE BUILD WITH YOU program, the following enhanced Firmware Customization Services are available on a project-basis to meet various enterprise customer needs in Server, Storage and Compute.

## Power Loss Protection (PLP) Tuning

**Optimized Flush Cache Timing.** Ensures that the flush cache is completed within the capacitors' hold-up time to ensure the integrity of data in flight and at rest. **PLP Capacitor Monitoring.** Performed using the on-board micro-controller unit (MCU), includes regular capacitor health checks during SSD boot-up and operation.

### Performance Behavior Tuning

Performance behavior analysis and customization to optimize throughput and latency in a customer host application

### Thermal Management Customization

ATP's thermal throttling solution is distinguished by the ability to adjust the temperature settings according to the customer's application-specific requirements.

## **SMART ID Customization**

The firmware includes a range of Self-Monitoring, Analysis and Reporting Technology (SMART) ID attributes which can be customized based on customer requirements.

## Download Microcode Capability

This service is part of flexible firmware maintenance, enabling Enterprise customers to rapidly make updates to their specific configurations via field updates, avoiding the hassle of sending SSDs back to ATP for reinitialization.

To ensure smooth DLMC (Download Microcode) operations during firmware verification or updates, especially when there are varying platform requirements during the validation process, ATP can provide multiple firmware binaries, allowing for testing flexibility.

This has resulted in strengthened DLMC Testing for Upload, Sideload, and Download. Building on the FW Field Update service, we perform DLMC testing between the new firmware version and its previous iterations. This includes ensuring successful self-updates for smoother transitions between different firmware versions or configurations during the customer's validation process.

## **Enhanced Read Disturb Resilience**

The FW algorithm ensures data integrity when data is frequently accessed by the host. ATP firmware will monitor the data and reprogram it to prevent data damage. This is especially important in read-only applications.

Frequent data reads are critical in read-only applications. ATP firmware is optimized to monitor and refresh data by implementing the "early move" (proactive approach) and "read reclaim" (reactive approach) algorithm. "Early move" refers to the moving of data to a different block when the error meets certain criteria of error threshold as defined by ATP. "Read reclaim" is activated by the frequency at which data is read to prevent data damage and ensure data integrity.

This feature validates Enhanced Read Disturb Resilience specifically for the Enterprise customer's script.

The firmware is modified to enhance its ability to withstand Read Disturb events. These modifications are intended exclusively for specific use cases identical to the Enterprise customer's, such as Boot-Up scenarios.

< FC 法 册- 0

ĥ

# **Product Specification**

Product Line	N651Sie						
Interface	Gen4 x4						
Form Factor	M.2	U.2	E1.S				
Dimensions (mm)	80 x 22 x 3.85	100 x 69.85 x 15	118.75 x 33.75 x 9.5				
Flash Type		TLC					
Capacity	120 GB to 1.92 TB 480 GB to 7.68 TB						
Sequential Read (up to) 1,6,7	6,450 MB/s	6,000 MB/s	6,100 MB/s				
Sequential Write (up to) 1,6,7	6,050 MB/s	5,500 MB/s	6,000 MB/s				
Random Read (up to) <sup>2,6,7</sup>	1,100 KIOPS	1,100 KIOPS 820 KIOPS					
Random Write (up to) <sup>2,6,7</sup>	1,250 KIOPS 1,200 KIOPS						
Sustained Sequential Write (up to) <sup>3,6,7</sup>	3,000 MB/s 3,200 MB/s						
Sustained Random Write (up to) 4,6,7	250 KIOPS (1,000 MB/s) 320 KIOPS (1,280 MB/s)						
Endurance [DWPD] <sup>8</sup>	Available in 1, 2, and 5 DWPD configurations						
QoS 99.9999% <sup>5,6,7</sup>	Read <90µs   Write <10µs	Read <80µs   Write <10µs	Read <80µs   Write <10µs				
Data Retention	1 year at 55°C (100% P/E cycles)						
Power Loss Protection	Yes						
End to End Data Path Protection	Yes						
Sustained Read Power (Max) <sup>7</sup>	<9W	<14.5W	<13W				
Sustained Write Power (Max) <sup>7</sup>	<11.5W	<17.5W	<15.5W				
Supply Voltage	3.3V 12V						
Operating Temperature Tc	-40°C to 85°C (I-Temp)						
Storage Temperature Tc	-40°C to 85°C						
Vibration	Sine 16.4G,10~2,000Hz						
Shock	Half sine 1,500G/0.5ms						
MTBF @ 25°C	> 3,000,000 hours						
UBER	<1 sector per 10^17 bits read						
Warranty	5 years						
Notes:							

1. Sequential Burst Performance tested with IOmeter 4MB, QD64

2. Random Burst Performance tested with IOmeter 4KB, QD64

3. Average Sustained Sequential Write Performance tested with IOmeter,

5.4KB Random QD=1

6. Actual performance may vary depending on user conditions and system environment

7. Parameters tested with highest capacity drive

- 8. DWPD for 5 years tested with JESD219A Enterprise workload
- 4. Average Sustained Random Write Performance tested with IOmeter, 4KB, QD64 for 4 hours

4MB, QD64 for 4 hours

Hot Items Ordering Information						
Target Usage	Endurance rating	Capacity	PCIe <sup>®</sup> Gen4 NVMe M.2 SSD	PCIe <sup>®</sup> Gen4 NVMe E1.S SSD	PCIe <sup>®</sup> Gen4 NVMe U.2 SSD	
Boot	1 DWPD	240 GB	FT240GP48APHBSI-ERS1			
		480 GB	FT480GP48APHBSI-ERS1			
		960 GB	FT960GP48APHBSI-ERS1	FT960GES4APHBSI-ERS1	FT960GU24APHBSI-ERS1	
		1.92 TB	FT1T92P48APHBSI-ERS1	FT1T92ES4APHBSI-ERS1	FT1T92U24APHBSI-ERS1	
		3.84 TB		FT3T84ES4APHBSI-ERS1	FT3T84U24APHBSI-ERS1	
		7.68 TB		FT7T68ES4APHBSI-ERS1	FT7T68U24APHBSI-ERS1	
Read Intensive	2 DWPD	200 GB	FT200GP48APHBSI-ERS2			
		400 GB	FT400GP48APHBSI-ERS2			
		800 GB	FT800GP48APHBSI-ERS2	FT800GES4APHBSI-ERS2	FT800GU24APHBSI-ERS2	
		1.60 TB	FT1T60P48APHBSI-ERS2	FT1T60ES4APHBSI-ERS2	FT1T60U24APHBSI-ERS2	
		3.20 TB		FT3T20ES4APHBSI-ERS2	FT3T20U24APHBSI-ERS2	
		6.40 TB		FT6T40ES4APHBSI-ERS2	FT6T40U24APHBSI-ERS2	
Mixed Use/Write Intensive	5 DWPD	120 GB	FT120GP48APHBSI-ERS3			
		240 GB	FT240GP48APHBSI-ERS3			
		480 GB	FT480GP48APHBSI-ERS3	FT480GES4APHBSI-ERS3	FT480GU24APHBSI-ERS3	
		960 GB	FT960GP48APHBSI-ERS3	FT960GES4APHBSI-ERS3	FT960GU24APHBSI-ERS3	
		1.92 TB		FT1T92ES4APHBSI-ERS3	FT1T92U24APHBSI-ERS3	
		3.84 TB		FT3T84ES4APHBSI-ERS3	FT3T84U24APHBSI-ERS3	



The Global Leader in Specialized Storage and Memory Solutions



# Follow us on

ATP Website





#### **ATP TAIWAN** Headquarters

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com 10F, No. 185, Tiding Blvd. Sec. 2, Neihu, Taipei, Taiwan 11493

### ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com Daimon Urbanist 602, 2-3-6 Shiba Daimon, Minato-ku, Tokyo 105-0012, Japan

#### v2 012025

© Copyright 2025 ATP Electronics, Inc. All rights reserved. Specifications or details may change without notice. All trademarks and registered trademarks are the property of their respective owners.

ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com 2590 North First Street, Suite #150 , San Jose, CA 95131, USA

#### ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com Max-Planck-Str. 5, D-85716 Unterschleißheim, Germany

## ATP INDIA

sales-india@atpinc.com

www.atpinc.com

## ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com 2F, Building 15, No. 115, Lane 572, Bibo Road, Zhangjiang High-Tech Park Pudong, Shanghai, China 201203

Printed on fully recyclable paper.