

## **USB 2.0 NANODURA**

The Global Leader in Specialized Storage and Memory Solutions



## **KEY FEATURES**

- Global wear leveling
- Bad block management algorithm
- High reliability
- Plug and Play with hot-swappable connection supported

The ATP NANODURA is an industrial USB drive built for mission-critical embedded applications. Suitable for compact systems installed in limited spaces, NANODURA's rugged metal housing and ATP System in Package (SiP) technology offer rugged durability for dependable use in extreme operating temperatures ranging from -40°C to 85°C and resistance to water/moisture, vibration, shock and electrostatic discharge (ESD).

NANODURA offers up to 60,000 program/erase (P/E) cycles, which is 20X higher than other USB drives in the market. The extraordinary endurance, advanced bad block algorithm and global wear leveling make NANODURA an excellent boot drive and ideal storage solution for applications with high performance and high data retention requirements. Hot swap support guarantees maximum availability, allowing drive removal and replacement without shutting down the system.

Technol	ogies	S.M.A.R.T/ Life Monitor	Industrial Temperature	SiP	Firmware-Based Power Loss Protection	Advanced Wear Leveling
Premium		0	0	0	0	0
Superior		0		0	0	0

## Specifications

Product Line	Premium	Superior			
FIODUCELINE	B800Pi	B600Sc			
Interface	USB 2.0 (480 Mbps)				
Flash Type	SLC	MLC			
Form Factor	USB	Туре-А			
Operating Temperature	-40°C to 85°C	0°C to 70°C			
Power Loss Protection Options	Firmware Based				
<b>Optional SED Features</b>		-			
Capacity	512 MB to 8 GB	4 GB to 8 GB			
	Performance				
Sequential Read (MB/s) up to	21	25			
Sequential Write (MB/s) up to	17	18			
	Endurance and Reliability				
Endurance (TBW) <sup>1</sup> up to	192 TB	19 TB			
Reliability MTBF @ 25°C	>5,000,000 hours	>2,000,000 hours			
Reliability Number of Insertions	10,000 minimum				
	Others				
Dimensions (mm)	34 x 12.2 x 4.5				
Certifications	CE, FCC, UKCA, RoHS				
Warranty	5 years	2 years			

1. Under highest Sequential write value. May vary by density, configuration and applications.



The Global Leader in Specialized Storage and Memory Solutions



Product spec and its related information are subject to change without advance notice. Please refer to <u>www.atpinc.com</u> for latest information v1.0 012025

© Copyright 2025 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368 sales-apac@atpinc.com ATP USA TEL: +1-408-732-5000 sales@atpinc.com **ATP EUROPE** TEL: +49-89-374-9999-0 sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797 sales-japan@atpinc.com ATP CHINA TEL: +86-21-5080-2220 sales@cn.atpinc.com ATP INDIA

sales-india@atpinc.com