



# SD/SDHC/SDXC Card

The Global Leader in Specialized Storage and Memory Solutions



## KEY FEATURES

- High endurance
- Compliant with Video Speed Class V30\*
- Robust data integrity\* (AutoRefresh and Dynamic Data Refresh)
- Power Loss Protection for data at rest
- I-Temp operable\* ( -40°C to 85°C)
- Continuous supply of SLC NAND to support existing (legacy) platforms
- Water/Dustproof and ESD-resistant System-in-Package design
- SD Life Monitor\*

\* May vary by product and project support

ATP SD cards are the ideal storage format for industrial and automotive applications as they can be conveniently inserted into and easily removed from small host devices for convenient data transfer and storage expansion.

Made to perform dependably under rigorous conditions, ATP SD cards are designed with extensive longevity, which is typically required in industrial applications such as automation, networking, health care and more.

ATP SD cards also deliver the quality, durability and reliability to meet the requirements of major automotive OEM/Tier 1 suppliers, system developers and service providers for higher levels of data accuracy, consistency and integrity in applications such as maps/navigation systems, in-vehicle infotainment (IVI), Advanced Driver Assistance Systems (ADAS), and other data- intensive applications. These solutions can withstand extreme temperatures, dust and shock/vibration, and maintain data integrity under power cycling or sudden power-off events.

Now available in 3D triple-level cell (TLC) NAND flash with A1 Performance Class rating, ATP SD cards undergo endurance, data retention and wide temperature tests and are certified according to international, automotive-specific and temperature-related standards.

## Specifications

Product Line	Premium		Superior
	S800Pi	S750Pi / S750Pc	S650Si / S650Sc
Interface	512 MB to 2 GB, HS mode 4 GB to 8 GB, UHS-I		UHS-I
Flash Type	SLC	3D TLC (pSLC mode)	3D TLC
Form Factor		SD Card	
Operating Temperature	-40°C to 85°C	-40°C to 85°C / -25°C to 85°C	
Power Loss Protection Options		Firmware Based	
Optional SED Features		-	
Capacity	512 MB to 8 GB	16 GB to 256 GB	32 GB to 512 GB
	Performance		
Sequential Read (MB/s) up to	81	95	95
Sequential Write (MB/s) up to	39	80	70
	Endurance and Reliability		
Endurance (TBW) <sup>1</sup> up to	192 TB	25,000 TB	5,500 TB
Reliability MTBF @ 25°C	>5,000,000 hours	>3,000,000 hours	>2,000,000 hours
Reliability Number of Insertions	20,000 (SDA spec minimum 10,000)		
	Others		
Dimensions (mm)	32.0 x 24.0 x 2.1		
Certifications	CE, FCC, UKCA, RoHS		
Warranty	5 years		3 years

1. Under highest Sequential write value. May vary by density, configuration and applications.

Technologies	S.M.A.R.T./ Life Monitor	Industrial Temperature	SiP	Firmware-Based Data-At-Rest Power Loss Protection	Advanced Wear Leveling	AutoRefresh	Dynamic Data Refresh	Auto-Read Calibration	Content Preload	Joint Validation and Test
Premium	S750Pi / S750Pc	▲	○	○	○	○	○	○	▲	▲
Superior	S650Si / S650Sc	▲	○	○	○	○	○	○	▲	▲

▲: Customization option available on a project basis.



The Global Leader in Specialized Storage and Memory Solutions

**WE BUILD WITH YOU**

Product spec and its related information are subject to change without advance notice.

Please refer to [www.atpinc.com](http://www.atpinc.com) for latest information

v1 022026

© Copyright 2026 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368  
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000  
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0  
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797  
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220  
sales@cn.atpinc.com

ATP INDIA

sales-india@atpinc.com