



PCIe® Gen3 NVMe M.2 SSD

The Global Leader in Specialized Storage and Memory Solutions



KEY FEATURES

- Power Loss Protection: MCU-based* with data-at-rest and in-flight protection
- Security: Self-Encrypting Drive (SED) with AES 256-bit encryption, TCG Opal 2.0*
- End-to-End Data Path Protection
- Thermal heatsink solutions**

* May vary by product and project support

** Customization available on a project basis

ATP's M.2 2280 NVMe solid state modules based on the NVMe™ protocol and leveraging the PCI Express® (PCIe®) Gen3 x4 interface deliver speedy, reliable, and enduring performance to fulfill the increasing data storage demands of today's embedded and industrial applications.

Constructed with 3D triple level cell (TLC) NAND flash, these modules are available in different capacities, ranging from 40 GB to 1 TB, to meet diverse data storage needs.

ATP NVMe SSDs with industrial operating temperature rating deliver stable performance even in extreme temperatures ranging from -40°C to 85°C.

Select ATP M.2 2280 NVMe modules adopt a Customizable Thermal Management Solution. This includes firmware and hardware options, such as copper foil and fin-type heatsink, to effectively dissipate heat and ensure optimal levels of sustained performance.

Specifications

Product Line	Value	Momentum	Value	Premium	Value		
	N650Vi / N650Vc	N400Mw	N650Vi / N650Vc	N700Pi / N700Pc	N600Vi / N600Vc		
Interface	PCIe G3 x4						
Flash Type	3D TLC		3D TLC (pSLC mode)		3D TLC		
Form Factor	M.2 2280 S2-M	M.2 2280 S2-M	M.2 2242 D5-M	M.2 2230-S4-M			
Operating Temperature	-40°C to 85°C / 0°C to 70°C	-20°C to 75°C	-40°C to 85°C / 0°C to 70°C				
Power Loss Protection Options	Firmware Based						
Optional SED Features	AES 256-bit Encryption, TCG Opal 2.0	AES 256-bit Encryption	-	AES 256-bit Encryption, TCG Opal 2.0	-		
Capacity	120 GB to 960 GB	128 GB to 1 TB	120 GB to 960 GB	40 GB to 160 GB	120 GB to 480 GB		
Performance							
Sequential Read (MB/s) up to	2,600	2,600	2,600	2,000	2,050		
Sequential Write (MB/s) up to	1,880	1,800	1,880	1,600	1,550		
Random Reads IOPS up to	250,800	240,000	250,800	135,600	138,000		
Random Writes IOPS up to	276,000	300,000	276,000	112,000	112,600		
Endurance and Reliability							
Endurance (TBW) ¹ up to	4,800 TB	695 TB	4,800 TB	4,280 TB	765 TB		
Reliability MTBF @ 25°C	>3,000,000 hours			>2,000,000 hours			
Others							
Dimensions (mm)	80.0 x 22.0 x 2.2			42.0 x 22.0 x 3.6	30.0 x 22.0 x 2.5		
Certifications	CE, FCC, BSMI, UKCA, RoHS, REACH						
Warranty	3 years	2 years	3 years	5 years	3 years		

1. Under highest Sequential write value. May vary by density, configuration and applications.

Technologies	S.M.A.R.T/ Life Monitor	Industrial Temperature	Firmware-Based Data-At-Rest Power Loss Protection	Advanced Wear Leveling	AutoRefresh	Dynamic Data Refresh	Auto-Read Calibration	ETEDP	SED	Software Secure Erase
Value N650Vi / N650Vc	○	○	○	○	○	○	○	○	▲	○
Momentum N400Mw	○		○	○	○	○	○	○	▲	○
Premium N700Pi / N700Pc	○	○	○	○	○	○	○	○	○	○
Value N600Vi / N600Vc	○	○	○	○	○	○	○	○		○

▲: Customization option available on a project basis.



Product spec and its related information are subject to change without advance notice.

Please refer to www.atpinc.com for latest information

v1 022026

© Copyright 2026 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
sales@cn.atpinc.com

ATP INDIA

sales-india@atpinc.com