



PCIe® Gen4 NVMe U.2 SSD

The Global Leader in Specialized Storage and Memory Solutions



KEY FEATURES

- Endurance: 1 DWPD (5 years Enterprise workload)
- Sustained Write Performance: Up to 3,000 MB/s
- Data Retention: Up to 10 years at 55°C (pSLC)*
- Power Loss Protection: MCU-based* with data-at-rest and in-flight protection
- PLP Diag*(Self-Diagnosing Capacitor Check)
- Security: Self-Encrypting Drive (SED) with AES 256-bit Encryption, TCG Opal 2.0*
- End-to-End Data Path Protection
- 15 mm integrated fin-type heatsink enclosure

* May vary by product and project support

ATP U.2 SSDs support the NVMe™ protocol on the high-speed PCI Express® (PCIe®) Gen4 x4 interface. Capacities range from 320 GB to 7.68 TB and can either be I-Temp (-40°C to 85°C: N751Pi/N651Si) or C-Temp (0°C to 70°C: N651Sc) operable to meet the varied usage requirements of embedded/ industrial PCs, networking systems, and other function-critical segments.

The high-speed PCIe Gen 4 x4 interface offers twice the bandwidth of the previous generation, enabling the N751Pi/N651Si/N651Sc U.2 SSDs to transfer data faster. ATP's PCIe Gen 4 SSDs use x4 lanes for a maximum bandwidth of 8 GB/s.

The 15 mm fin-type heatsink design offers effective heat dissipation to ensure optimal sustained performance.

Specifications

Product Line	Premium	Superior
	N751Pi	N651Si / N651Sc
Interface	PCIe G4 x4	
Flash Type	3D TLC (pSLC mode)	3D TLC
Form Factor	U.2	
Operating Temperature	-40°C to 85°C	-40°C to 85°C / 0°C to 70°C
Power Loss Protection Options	Hardware + Firmware Based	
Optional SED Features	AES 256-bit Encryption, TCG Opal 2.0	
Capacity	320 GB to 2.56 TB	960 GB to 7.68 TB
Performance		
Sequential Read (MB/s) up to	6,100	6,000
Sequential Write (MB/s) up to	6,000	6,000
Random Reads IOPS up to	870,000	
Random Writes IOPS up to	1,250,000	1,230,000
Endurance and Reliability		
Endurance (TBW) ¹ up to	486,000 TB	76,000 TB
Reliability MTBF @ 25°C	>3,000,000 hours	
Others		
Dimensions (mm)	100 x 69.85 x 15	
Certifications	RoHS, VCCI, CE, FCC, UKCA	CE, FCC, UKCA, VCCI, RoHS, REACH
Warranty	5 years	3 years

1. Under highest Sequential write value. May vary by density, configuration and applications.

Technologies	S.M.A.R.T/ Life Monitor	PLP Diag	Industrial Temperature	Firmware-Based Power Loss Protection	Hardware-Based Power Loss Protection	Advanced Wear Leveling	AutoRefresh	Dynamic Data Refresh	Auto-Read Calibration	ETEDP	SED	Software Secure Erase
Premium	N751Pi	○	○	○	○	○	○	○	○	○	○	○
Superior	N651Si	○	○	○	○	○	○	○	○	○	○	○



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

Product spec and its related information are subject to change without advance notice.

Please refer to www.atpinc.com for latest information

v1 022026

© Copyright 2026 ATP Electronics, Inc. All rights reserved.

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
sales@cn.atpinc.com

ATP INDIA

sales-india@atpinc.com